


SHANGHAI CIPHY INDUSTRY CO.,LTD.

ANSI CLASS 600/800/1500 FOR FORGED CARBON STEEL OR STAINLESS STEEL Y-GLOBE VALVE BOLTED BONNET DESIGN

MODEL NO: FBAXTH-YT



Y-GLOBE VALVE PRODUCT'S SIZE:

PRESSURE GRADE	FROM	TO
CLASS 600	1/2"	2"
CLASS 800	1/2"	2"
CLASS 1500	1/2"	2"

DESIGN DESCRIPTION:

- * Y-TYPE BOLTED BONNET O. S & Y TYPE
- * OPTIONAL: WELD BONNET O. S & Y TYPE
- * WEDGE DISC, RENEWABLE SEAT RING
- * CONNECTRION: THREADED END, SOCKETED END
- * THREAD TYPE(NPT, BSPT, DIN ENDS)
- * MATERIAL: A105, F304, F316, F11, F22, F304L, F316L

WORKING PRESSURE AND TEMPERATURE

WORKING TEMPERATURE		
MATERIAL	CELSIUR SCALE	FAHRENHEIT
CARBON STEEL	-29 ⁰ C~425 ⁰ C	6 ⁰ F~822 ⁰ F
STAINLESS STEEL	-40 ⁰ C~550 ⁰ C	15 ⁰ F~1047 ⁰ F

GENERAL DESIGN SPECIFICATIONS:

ITEM	CLASS 600	CLASS 800	CLASS 1500
MANUFACTURE	API 602	API 602	API 602
PRESSURE-TEMPERATURE RATINGS	ANSI B16.34	ANSI B16.34	ANSI B16.34
END TO END	ANSI B16.10	ANSI B16.10	ANSI B16.10
END THREAD	ANSI B 1.20.1	ANSI B 1.20.1	ANSI B 1.20.1
SOCKET-WELDING	ANSI B 16.11	ANSI B 16.11	ANSI B 16.11
INSPECTION AND TEST	API 598		

TEST PRESSURE TO API598

ANSI	SHELL (WATER)		SEAT (WATER)		SEAT (AIR)		BACK SEAT (WATER)	
CLASS 600	15.3MPA	2225PSI	11.2MPA	1630PSI	0.6MPA	80PSI	11.2MPA	1630PSI
CLASS 800	21MPA	3000PSI	15.4MPA	2200PSI	0.6MPA	80PSI	15.4MPA	2200PSI
CLASS 1500	38.7MPA	5500PSI	28.1MPA	4000PSI	0.6MPA	80PSI	28.1MPA	4000PSI

TRIMS SPECITIED DUE TO TABLE 3:


DISC SEAT SURFACE PART NO.2	BODY SEAT SURFACE PART	STEM PART NO.3
F6	F6	F6
STELLITE	STELILITE	F6
F6	STELILITE	F6
F304	F304	F304
F316	F316	F316

OTHER MATERIALS ARE AVAILABLE UPON REQUEST.

PARTS AND MATERIAL (ASTM)

NO.	PARTS NAME	MATERIALS				
1	BODY	ASTM A105	ASTM F304	ASTM F316	ASTM F304L	ASTM F316L
4	GASKET	GRAPHITE+304		GRAPHITE+316		
5	BONNET	ASTM A105	ASTM F304	ASTM F316	ASTM F304L	ASTM F316L
6	BONNET BLOT	ASTM A193 B7	ASTM A193 B7			
7	STEM PACKING	REINFORCED GRAPHITE				
8	GLAND	ASTM A276 410	ASTM F304L	ASTM F316L	ASTM F304L	ASTM F316L
9	GLAND FLANGE	ASTM A216 WCB	ASTM F304	ASTM F316	ASTM F304L	ASTM F316L
10	GLAND EYEBOLT	ASTM A193 B7	ASTM A193 B8			
11	GLAND NUT	ASTM A194 2H	ASTM A194 B8			
12	STEM NUT	ASTM A276 410	ZcuAl10Fe3			
13	HAND WHEEL	ASTM A197				
14	H.W.LOCK NUT	ASTM A194 2H	ASTM A194 B8			

OTHER MATERIALS ARE AVAILABLE UPON REQUEST.

**DIMENSIONS LIST(UNIT:MM):**

DN	SIZE	S(THREAD)	S(SOCKET)	L	H(OPNE)	W	WEIGHT(KG)
15	1/2"	1/2"	21.8	98	240	100	2.3
20	3/4"	3/4"	27.1	98	240	100	3.6
25	1"	1"	33.8	120	290	125	7.8
32	1-1/4"	1-1/4"	42.6	140	302	160	8.2
40	1-1/2"	1-1/2"	48.7	140	368	160	12.0
50	2"	2"	61.1	170	370	180	15.0

*** We hereby reserve the rights of any alternative dimension that would help to improve our valve's quality and working efficiency**



SHANGHAI CIPHY INDUSTRY CO.,LTD
7G-1 Building, N0.515 Yishan Rd.
Shanghai, China
TEL:+86-21-5497 5962
FAX:+86-21-5497 5963
HTTP://WWW.CIPHY.CN
CIPHY@CIPHY.COM
COPYRIGHT©2004-[CIPHY]
ALL RIGHTS RESERVED.