


SHANGHAI CIPHY INDUSTRY CO.,LTD.

Marine Valve JIS F7358/7359


MODEL NO: JIS- F7358/7359



MAIN DATA FOR JOINING(mm)

DN	L	D	C	n-d	t	H'	D ₁	Weight (kg)
50	210	130	105	4-15	16	107	140	11.3
65	250	155	130	4-15	18	124	160	16.8
80	280	180	145	4-19	18	129	190	23.2
100	340	200	165	8-19	20	146	215	32.5
125	410	235	200	8-19	20	166	245	48.1
150	480	265	230	8-19	22	188	270	67.9
200	570	320	280	8-23	24	212	335	115.0

Marine Cast Iron Lift Check Globe Valves JIS F7358 5K



MAIN DATA FOR JOINING(mm)

DN	L ₁	D	C	n-d	t	H'	D ₁	Weight (kg)
50	100	130	105	4-15	16	77	140	9.5
65	115	155	130	4-15	18	81	160	13.8
80	130	180	145	4-19	18	84	190	18.9
100	150	200	165	8-19	20	96	215	25.6
125	170	235	200	8-19	20	108	245	36.7
150	190	265	230	8-19	22	125	270	50.9
200	220	320	280	8-23	24	157	335	95

Marine Cast Iron Lift Check Angle Valves JIS F7359 5K

Applicable scope:

The products are used for preventing reflux in fuel oil piping, lubricating oil piping and water piping at temperatures 120°C or less. Dimensions of flange are according to JIS B2220 flange dimensions of steel pipe.

Materials of major parts:

Part name	Material			
	Name	Mark	Name	Mark
Body, Bonnet	Cast iron	HT200	Cast iron	QT400-15
Disc, Seat	Stainless steel	2Cr13		

Capability:

Nominal Pressure	5kgf/cm ² (0.49Mpa)
Seal Pressure	7.7kgf/cm ² (0.761Mpa)
Intensity Pressure	10.5kgf/cm ² (1.046Mpa)

Medium	Max Pressure kgf/cm ² (Mpa)
Oil&flow water	5 kgf/cm ² (0.49Mpa)
Lenitic water ≤ 120°C	7 kgf/cm ² (0.69Mpa)



SHANGHAI CIPHY INDUSTRY CO.,LTD
 7G-1 Building, N0.515 Yishan Rd.
 Shanghai, China
 TEL:+86-21-5497 5962
 FAX:+86-21-5497 5963
 HTTP://WWW.CIPHY.CN
 CIPHY@CIPHY.COM
 COPYRIGHT©2004-[CIPHY]
 ALL RIGHTS RESERVED.